



Technical Data Sheet

Product	Type
----------------	-------------

COOLSURF™ RCO-70

Metal Processing

Ethanolamine-free alkanolamide

Application

Coolsurf RCO-70 is an amide resulting from the reaction of diisopropanolamine and a vegetable oil rich in oleic acid

Coolsurf RCO-70 is an excellent co-emulsifier providing excellent oxidative stability, good boundary lubrication, high reserve alkalinity and excellent corrosion protection for soluble oils, semi-synthetics, synthetics, and cleaners.

Typical Properties

Test	Typical
Appearance	Amber, viscous fluid
Specific gravity at 15.6° C	0.96
pH at 1%	10
Total base number mg KOH/g	50
Water wt. %	3

Benefits

- Water soluble and dispersible in oil
- Very low foam
- High reserve alkalinity
- Good emulsifying properties
- Boundary lubrication and oxidative stability
- Non-staining on aluminum
- Excellent hard water stability
- Dispersible in oil and water

Suggested Formulation Details

Semi-synthetic fluid concentrate

PART I

First: Prepare the oil phase as follows

100 SUS naphthenic oil.....	63.0%
Coolsurf RCO-70	14.0%
Counter Rust™ HW-100	2.0%
Tall Oil 25/30 rosin acid.....	8.0%
Glycol Ether TPnB.....	8.0%
TMP oleate.....	5.0%

PART II

Second: Add oil phase into water while mixing

Water	20% - 35%
Counter Rust T-43	11.5% - 12.5%
Part I (Oil Phase)	50% - 65%
Defoamer0% - 0.2%
Fungicide0% - 1.0%

RECOMMENDED USAGE

	<u>Fluid Concentrate</u>	<u>Water</u>
General Machining	5 – 7%	Balance
Heavy-Duty Machining	10 – 12%	Balance

Storage and Handling

Recommended Maximum Long Term Storage Temperature	Ambient
Recommended Minimum Temperature for Use	Ambient
Flash Point	>190° C COC



TRU Full Circle Additives

Technical Data Sheet
810-776-8440
www.truadditives.com

TRU Full Circle Additives

4302 James P Cole Boulevard Flint, MI 48505
Phone: 1-810-776-8440 Fax 1-810-776-8540
www.truadditives.com
customerservice@truadditives.com

DISCLAIMER: To the best of our knowledge, the information and recommendations contained herein are accurate. However, this information and recommendations are furnished without any warranty, representation or license of any kind. Users of our products are encouraged to run their own tests to ensure product fitness for their applications. Furthermore, users assume sole liability for any patent infringement that occurs by reason of following our recommendations or using the information given