



Technical Data Sheet

Product	Type
----------------	-------------

COUNTER RUST™ 6000

Metal Protection
Oxide of a petroleum wax

Application

Counter Rust 6000 is a mixture of relatively high molecular weight organic acids, lactones and ester derived from the high pressure oxidation of petroleum fractions. Counter Rust 6000 is primarily used as a chemical intermediate in the formulation of rust preventive and metalworking formulations.

Metal soaps (e.g. zinc or calcium) of Counter Rust 6000 are proven effective in formulating rust preventives effective against salt spray, humidity or acid atmospheres.

Typical Properties

Test	Typical
Appearance	Waxy solid
Specific gravity at 25° C	0.93
Total acid number, mg KOH/g	50
Total saponification number, mg KOH/g	110
Congeval melt point, °C	60

Benefits

- Economic and effective chemical intermediate for formulating rust preventive.
- Worldwide registrations including REACH
- Excellent wetting properties
- Boost corrosion protection and lubricity when neutralized.

Storage and Handling

Recommended Maximum Long Term Storage Temperature	Ambient
Flash Point	190°C



TRU Full Circle Additives

4302 James P Cole Boulevard Flint, MI 48505
Phone: 1-810-776-8440 Fax 1-810-776-8540

www.truadditives.com
customerservice@truadditives.com

DISCLAIMER: To the best of our knowledge, the information and recommendations contained herein are accurate. However, this information and recommendations are furnished without any warranty, representation or license of any kind. Users of our products are encouraged to run their own tests to ensure product fitness for their applications. Furthermore, users assume sole liability for any patent infringement that occurs by reason of following our recommendations or using the information given