



Technical Data Sheet

Product	Type
----------------	-------------

EZ-MULZ™ 4037

Metal Processing

Premium Emulsifier Base for Naphthenic Oils

Application

EZ-Mulz 4037 is a unique, sulfonate-free emulsifier base designed to emulsify naphthenic oils with aniline points of 195° F or lower.

Based on nonionic and anionic emulsifiers, corrosion inhibitors, buffering agents and other component, EZ-Mulz 4037 is ideal for formulating soluble and semi-synthetic metalworking fluids.

EZ-Mulz 4037 is free from chlorine, nitrites, phenols and heavy metals and is non-staining on aluminum

Typical Properties

Test	Typical
Appearance	Clear, reddish liquid
Specific gravity at 25° C	1.0
Water wt. %	5.0
Total acid number, mg KOH/g	50
pH at 1.0% in water	8.7

Benefits

- Excellent emulsion stability in all naphthenic oils
- Good lubricity and EP properties
- Low foam and hard water stable
- Good corrosion protection in for ferrous metals
- Compatible with extreme pressure additives such as chlorinated or sulfurized compounds

Performance

Corrosion on cast iron ships – ASTM D-4627-92
Ratings scale: 0 = no rust and 5 = 100% rust

5% emulsion of 15% EZ-Mulz 4037 in oil.....0

Typical Applications

General-purpose soluble oil

100 SUS naphthenic oil	81 - 85%
EZ-Mulz 4037	15%
Biocide	0 – 3%
Fungicide	0 – 1%

Heavy-duty soluble oil

100 SUS naphthenic oil	71 - 75%
EZ Mulz 4037	25%
Biocide	0 – 3%
Fungicide	0 – 1%

Semi-Synthetic Fluid Concentrate

Part I – Oil Phase

100 SUS naphthenic oil	44%
EZ Mulz 4037	50%
Biocide	5%
Fungicide	2%

Part II Add oil phase to water while mixing

Water	55-60%
Oil phase	40-45%

Recommended use of semi-synthetic concentrate

General machining	5-10%
Heavy-duty machining	10-20%

Storage and Handling

Recommended Maximum Long Term Storage Temperature*	Ambient
Recommended Minimum Temperature for Use	Ambient
Flash Point	>150°C COC

*Do not store with excessive heat (>150° F) over long periods.



TRU Full Circle Additives

Technical Data Sheet

810-776-8440

www.truadditives.com

TRU Full Circle Additives

4302 James P Cole Boulevard Flint, MI 48505

Phone: 1-810-776-8440 Fax 1-810-776-8540

www.truadditives.com

customerservice@truadditives.com

DISCLAIMER: To the best of our knowledge, the information and recommendations contained herein are accurate. However, this information and recommendations are furnished without any warranty, representation or license of any kind. Users of our products are encouraged to run their own tests to ensure product fitness for their applications. Furthermore, users assume sole liability for any patent infringement that occurs by reason of following our recommendations or using the information given

EZ-Mulz is a Trademark of TRU Additives, LLC

2/1/2017