



# Technical Data Sheet

<b>Product</b>	<b>Type</b>
----------------	-------------

**EZ-MULZ™ 5609**

**Metal Processing**

**Emulsifier Base for Paraffinic Oil**

## Application

EZ-Mulz 5609 is an emulsifier base designed to emulsify paraffinic oils with high aniline points.

Based on natural sodium sulfonate, secondary emulsifiers and other components, EZ-Mulz 5609 is ideal for formulating soluble oils.

EZ-Mulz 5609 is free from chlorine, nitrites, phenols and heavy metals.

## Typical Properties

Test	Typical
Appearance	Dark brown, viscous fluid
Specific gravity at 25° C	1.01
Water wt. %	9.0
Total acid value, mg KOH/g	29
pH at 1.0% in water	8.6

## Benefits

- Excellent emulsion stability in all paraffinic oils
- Good corrosion protection in for ferrous metals
- Adds lubricity
- Compatible with extreme pressure additives such as chlorinated or sulfurized compounds

## Performance

Corrosion on cast iron ships – ASTM D-4627-92  
Ratings scale: 0 = no rust and 5 = 100% rust

**5% emulsion of 17% EZ-Mulz 5609 in oil.....0**

## Typical Applications

**EZ-Mulz 5609** can be used in several metalworking applications. For example:

*Use the following as a guideline, balance formula as needed*

### General-purpose soluble oil

	<u>% by weight</u>
150 SUS paraffinic oil .....	65 - 85
<b>EZ-Mulz 5609</b> .....	15 - 25
Chlorinated additive (Extreme pressure agent).....	0 - 20
Glycol ether (To modify viscosity) .....	0 - 1
Biocide .....	0 - 3
Fungicide .....	0 - 1
Defoamer, if necessary .....	0 - 1

*Adding some biocides may require the addition of tall oil fatty acid to balance the formula.*

## Storage and Handling

Recommended Maximum Long Term Storage Temperature*	Ambient
Recommended Minimum Temperature for Use	Ambient
Flash Point	>150°C COC

\*Do not store with excessive heat (>150° F) over long periods.



**TRU Full Circle Additives**

Technical Data Sheet

810-776-8440

[www.truadditives.com](http://www.truadditives.com)

### **TRU Full Circle Additives**

4302 James P Cole Boulevard Flint, MI 48505

Phone: 1-810-776-8440 Fax 1-810-776-8540

[www.truadditives.com](http://www.truadditives.com)

[customerservice@truadditives.com](mailto:customerservice@truadditives.com)

**DISCLAIMER:** To the best of our knowledge, the information and recommendations contained herein are accurate. However, this information and recommendations are furnished without any warranty, representation or license of any kind. Users of our products are encouraged to run their own tests to ensure product fitness for their applications. Furthermore, users assume sole liability for any patent infringement that occurs by reason of following our recommendations or using the information given

EZ-Mulz is a Trademark of TRU Additives, LLC

11/1/2017

