



Technical Data Sheet

Product	Type
----------------	-------------

EZ-MULZ™ 5900

Metal Processing

Hybrid Emulsifier Base for Paraffinic Oil

Application

EZ-Mulz 5900 is an emulsifier base designed to emulsify paraffinic oils with high aniline points. This product can also be used for naphthenic oils with minor adjustments for the HLB.

The primary emulsifying components are a blend of natural sodium sulfonate for initial emulsion formation (bloom) and PIBSA for longer term emulsion stability.

EZ-Mulz 5900 is free from chlorine, nitrites, phenols and heavy metals.

Typical Properties

Test	Typical
Appearance	Dark brown, viscous fluid
Specific gravity at 25° C	1.01
Water wt. %	6.0
Total acid value, mg KOH/g	25
pH at 1.0% in water	8.5

Benefits

- Excellent emulsion stability in all paraffinic oils
- Good corrosion protection in for ferrous metals
- Adds lubricity
- Compatible with extreme pressure additives such as chlorinated or sulfurized compounds

Performance

Corrosion on cast iron ships – ASTM D-4627-92
Ratings scale: 0 = no rust and 5 = 100% rust

5% emulsion of 15% EZ-Mulz 5900 in oil.....0

Typical Applications

EZ-Mulz 5900 can be used in several metalworking applications. For example:

Use the following as a guideline, balance formula as needed

General-purpose soluble oil

	<u>% by weight</u>
150 SUS paraffinic oil	65 - 85
EZ-Mulz 5900	15 - 25
Chlorinated additive (Extreme pressure agent).....	0 - 20
Biocide	0 - 3
Fungicide	0 - 1
Defoamer, if necessary	0 - 1

Adding some biocides may require the addition of tall oil fatty acid to balance the formula.

Storage and Handling

Recommended Maximum Long Term Storage Temperature*	Ambient
Flash Point	>150°C COC

*Do not store with excessive heat (>150° F) over long periods.



TRU Full Circle Additives
 Technical Data Sheet
 810-776-8440
www.truadditives.com

TRU Full Circle Additives

4302 James P Cole Boulevard Flint, MI 48505
 Phone: 1-810-776-8440 Fax 1-810-776-8540
www.truadditives.com
customerservice@truadditives.com

DISCLAIMER: To the best of our knowledge, the information and recommendations contained herein are accurate. However, this information and recommendations are furnished without any warranty, representation or license of any kind. Users of our products are encouraged to run their own tests to ensure product fitness for their applications. Furthermore, users assume sole liability for any patent infringement that occurs by reason of following our recommendations or using the information given