



Technical Data Sheet

Product

Type

SulfoGel™ 756

Metal Protection

Semi-Finished thixotropic calcium sulfonate coating

Application

SulfoGel 756 is a semi-finished coatings products that can be used directly or further formulated.

SulfoGel 756 is a thixotropic overbased calcium sulfonate and wax blend in a low aromatic mineral spirits.

It is an excellent long term rust preventive and has applications in cavity waxes, vehicle undercoatings, bridge coatings and frame coatings.

Typical Properties

Test	Typical
Pounds per gallon At 25° C	7.80
Brookfield viscosity @ 25° C	14,000
Non-volatile, wt. %	62
Water wt. %	1.0

Benefits

- Provides a barrier film with good anti-sag properties
- Highly resistant to chloride induced corrosion
- Excellent surface wetting agent
- High tolerance for dirty, oily or distressed surfaces

Storage and Handling

Recommended Storage Temperature	10-30° C
Flash Point	>61° C



TRU Full Circle Additives

4302 James P Cole Boulevard Flint, MI 48505

Phone: 1-810-776-8440 Fax 1-810-776-8540

www.truadditives.com

customerservice@truadditives.com

DISCLAIMER: To the best of our knowledge, the information and recommendations contained herein are accurate. However, this information and recommendations are furnished without any warranty, representation or license of any kind. Users of our products are encouraged to run their own tests to ensure product fitness for their applications. Furthermore, users assume sole liability for any patent infringement that occurs by reason of following our recommendations or using the information given